

STS 500

High Performance Separator Self-Cleaning Disk-Type Centrifuge



Highest Performance ... Proven Design

Technical Features:

- Valve-Type ejection system
- Liquid hermetic seal
- Gentle / Low shear feed design
- Adjustable ejection volume
- Enclosed solids discharge
- Short spindle + Cushioned drive
- Belt drive
- Upper & Lower centripetal pumps

Monitoring + Control:

- Process dependant ejection control
- Product flow rate auto-control
- Oil flow monitoring + control
- Vibration monitoring + control
- Bowl speed monitoring + control
- Air + Water pressure monitoring + control

Alternative Designs:

- Relocatable system
- Gas-tight design
- 2-phase clarifier or 3-phase separator design

Benefits:

- precise automatic solids discharge
- low oxygen pick-up
- higher clarification efficiency
- optimal ejection performance for application
- lower noise level
- minimises vibrational severity
- low maintenance cost
- discharge product streams under pressure

- determines time for optimal solids ejection

STS 500 General Specifications:

- Bowl material in EN 1.4418 (*)
- Other Product contact surfaces in 316 SS (or higher *)
- Painted cast frame (optional stainless clad design)
- Bowl speed 4,800 rpm
- 55 - 75 kW main motor (*)
- VFD + Resistance brake (key safety feature for VFD centrifuges)
- Alan Bradley CPU (*)
- Alan Bradley Panelview Plus Colour screen (*)
- (*) Alternatives upon request

Proven Design + User-Friendly Controls = High Performance



The STS 500 Operator Control Interface—customised to your requirements

Performance Capabilities:

Typical Applications:

- Brewing
- Wine
- Dairy
- Coffee + Tea
- Protein
- Fruit + Vegetable Juices
- Citrus
- Rendering
- Wastewater + Environmental
- Nutraceuticals



An STS Series Clarifier installation at a South African beverages plant

Flow Rates - Typical Applications:

Beer Polishing	95 - 120 m ³ /hr
Hot Wort Separation	70 - 75 m ³ /hr
Cold Wort Separation	50 - 60 m ³ /hr
Protein Recovery	35 - 45 m ³ /hr
Citrus Pulp Clarification	20 - 35 m ³ /hr
Essential Oil Concentration	20—25 m ³ /hr
NFC Top Oil Separation	35 - 45 m ³ /hr
Milk or Whey Skimming	45 - 50 m ³ /hr

Actual capacities are subject to the specific characteristics of the product & installation.

Price / Performance that separates the STS 500 above the rest

Contact:

Australia:

Global Head Office:

Separator Technology Solutions Pty Ltd
Melbourne, Australia

P:: +61 3 9016 4330
E: info@sts200.com
W: www.sts200.com

Sales Agent:

Australian Beverage Systems Pty Ltd
McLaren Vale, Australia

P: +61 407 842 244
E: price.geoff@bigpond.com

Argentina:

Sales & Service Agent:

Partner S.A.
Mendoza, Argentina

P: +56 2 429 2800
E: info@partnersa.cl
W: www.partner.cl

Chile:

Sales & Service Agent:

Partner S.A.
Santiago, Chile

P: +56 2 429 2800
E: info@partnersa.cl
W: www.partnersa.cl

France:

Sales & Service Office:

Separator Technology Solutions (FR) SARL
Paris, France

P: +33 6 23 67 72 46
E: sales_fr@sts200.com
W: www.sts200.com

New Zealand:

Sales & Service Agent:

Vintech Pacific Ltd
Gisbourne, New Zealand

P: +64 6 863 0024
E: info@vintechpacific.co.nz
W: www.armoritech.co.nz

USA - West Coast:

Sales & Service Office:

Separator Technology Solutions US Inc
San Francisco, CA, USA

P: +1 559 253 3699
E: info@sts200.com
W: www.sts200.com

Canada & USA - North East:

Sales & Service Agent:

Centrifuges Unlimited
Calgary & Ontario, Canada

P: +1 403 236 2883
E: infocui@centrifuges.net
W: www.centrifuges.net

South Africa:

Sales & Service Office:

Separator Technology Solutions (SA) Pty Ltd
Stellenbosch, South Africa

P:: +27 73 443 6257
E: info@sts200.com
W: www.sts200.com

Disclaimers:

This information serves as a non-binding description of our products and capabilities and does not constitute a guarantee of performance.

The STS 500 is supplied by Separator Technology Solutions and its approved local representatives. Any resemblance to, or compatibility of parts with, competitor models is of a functional design nature and strictly should not be misconstrued as having further meaning.